



OPUS

Recessed Trimless Track System - Trimless recessed track system featuring an aluminum extruded profile, including concealed comprehensive electrical system. All Opus profiles require a power feed module, Opus Nexu. Opus profiles may be added to create any desired length up to 72' (21m) per one power feed module. One connection kit included per profile piece to allow for additional profiles to be added.

Construction

- Standard 10' (304.8cm) modules constructed from anodized aluminum.
- Factory custom available between 2' (60.96cm) and 10' (304.8cm), please allow for additional lead time on factory custom profiles.
- Natural anodized or black anodized finishes available.
- Suitable for drywall, acoustic, wood, and various architectural ceilings with thicknesses of 3/8" (9.53mm) to 1 1/4" (31.75mm) with included adjustable drywall bracket.
- Made in Germany, Design by Porsche Design Studio

Related Fixtures

- AS313F - Opus Lux (Fixed LED Downlight)
- AS313A - Opus Lux Radius (Adjustable LED Downlight)
- AS413F - Opus Lac (Multi-Directional LED Downlight)

Mounting

- Mounting bracket included per profile to attach to existing structure.
- Profile must be mounted using threaded rod or other load rated attachment method to the existing structure.
- Final installation to be determined by licensed contractor.

Listings

- ETL Listed, Dry Location
- Airtight Listed.
- CCSA Chicago plenum



ORDERING INFORMATION

SERIES NO.	LENGTH	FINISH	POWER	OPTIONS
AS0 - Opus Profile	1 - 10' module X - factory custom 2-10'	NA - natural anodized BA - black anodized	0 - non-power feed *opus nexu required per 72' feet.	N - trimless

AS0 - __ - 0-N

ORDERING EXAMPLE AS06-BA-0-N

OPUS

