



OPUS NEXUS POWER SIDE FEED

Opus Profile Power Side Feed - The Opus Nexus is Apure's next generation power feed for the Opus multi-functional profile system. The Opus Nexus allows for easier access to the junction box during installation and for modifications. The Opus Nexus is required to electrify up to 72' (21m) and includes a connection kit, endcap and busway terminators.

Construction

- Formed steel and milled aluminum side feed.
- Available in natural and black anodized finishes.
- Compatible with all ASOX profile series.
- Nexus Dimensions: 5.66" x7.40" x1.97" (144x188x50mm)
- Made in Germany, Design by Porsche Design Studio.

Electrical

- 120V-277VAC 50/60Hz Input Voltage.
- 2 separate lighting circuit. Phase (ELV) dimmable (L1, L2, N1, N2)
- 1 audio circuit.
- 1 unswitched line accessory circuit.
- Compatible with Electronic Low Voltage reverse phase dimmers.
- For optimal performance, operate luminaire in conjunction with dimming switches or modules. Proper wiring and use of dimmers is to be performed by a qualified professional.

Related Products

- ASOX - Opus (Multi-Functional Profile)

Mounting

- The Opus Nexus is mounted at either end of the profile
- Only one Nexu required per 72' (21m) track composition.
- Final installation to be determined by licensed contractor.

Listings

- ETL Listed, Dry Location
- Airtight Listed
- CCSA Chicago plenum

Awards / Recognitions



reddot award 2016
winner lighting design



ORDERING INFORMATION

SERIES NO.	MODEL	FINISH	POWER FEED	OPTIONS
AS0- Opus Series	F - Side Feed	NA - natural anodized BA - black anodized	1 - 120V-277V AC	N - trimless

AS0F-__-1-N

ORDERING EXAMPLE AS0F-NA-1-N