



UNIVERSAL DRYWALL BRACKET

Description

The Universal Drywall Bracket allows for easy installation of Minus Series fixtures within existing and new drywall ceilings or walls. The bracket kit includes a pre-cut fermacell board for the specified Minus fixture to be installed onto. The fermacell board is then fastened to the bracket until it is flush with the existing drywall. The drywall is then finished and painted as desired.

Construction

- Formed steel frame
- Includes screws for mounting to existing drywall
- M5 Hardware
- The UN Construction board is constructed of gypsum fermacell and is pre cut to fit the required cutout in your drywall with .08" (2.2mm) allowance for taping, plastering and finishing.
- Bracket Dimensions: 11.85" x 8.46" (301mm x 215mm)
- Fiberboard Dimensions: 8"x 8" (200mm x 200mm)

Trimless Recessed Installation

- The Minus Universal Drywall Bracket and hardware allows for trimless installation of the Minus Series into existing drywall ceilings/walls or during new construction.
- Designed to provide precision alignment through the use of slotted holes.

Listings

- UL Listed, CE Conform
- Suitable for dry and wet locations

Installation Instructions/ Video

Scan QR Code or visit at apure-system.com/resources

US Standard Drywall Board

- Minus One: 18mm
- Minus Two: 15mm
- Minus Three: 18mm
- Minus Four: 15mm
- Minus Five : 15mm



ORDERING INFORMATION

SERIES

- AM - Minus Series

MODEL

- 1 - Minus One
 2 - Minus Two
 3 - Minus Three
 4 - Minus Four
 5 - Minus Five

CLASS

- BRK - Bracket

TYPE

- U10 - 10.5mm Board
 U12 - 12mm Board
 U15 - 15mm Board
 U18 - 18mm Board

ORDERING EXAMPLE

AM2BRKU15