



## UNIVERSAL DRYWALL BRACKET

### Description

The Universal Drywall Bracket allows for easy installation of Minus Series fixtures within existing and new drywall ceilings or walls. The bracket kit includes a pre-cut fermacell board for the specified Minus fixture to be installed onto. The fermacell board is then fastened to the bracket until it is flush with the existing drywall. The drywall is then finished and painted as desired.

### Construction

- Formed steel frame
- Includes screws for mounting to existing drywall
- M5 Hardware
- The UN Construction board is constructed of gypsum fermacell and is pre cut to fit the required cutout in your drywall with .08" (2.2mm) allowance for taping, plastering and finishing.
- Bracket Dimensions: 11.85" x 8.46" (301mm x 215mm)
- Fiberboard Dimensions: 8"x 8" (200mm x 200mm)

### Trimless Recessed Installation

- The Minus Universal Drywall Bracket and hardware allows for trimless installation of the Minus Series into existing drywall ceilings/walls or during new construction.
- Designed to provide precision alignment through the use of slotted holes.

### Listings

- UL Listed, CE Conform
- Suitable for dry and wet locations

### US Standard Drywall Board

- Minus One: 18mm
- Minus Two: 15mm
- Minus Three: 18mm
- Minus Four: 15mm
- Minus Five : 15mm

### Resources

Scan QR Code or visit at [apurelighting.com/resources/](http://apurelighting.com/resources/)



Resources

## ORDERING INFORMATION

### SERIES

- AM - Minus Series

### MODEL

- 1 - Minus One  
 2 - Minus Two  
 3 - Minus Three  
 4 - Minus Four  
 5 - Minus Five

### CLASS

- BRK - Bracket

### TYPE

- U10 - 10.5mm Board  
 U12 - 12mm Board  
 U15 - 15mm Board  
 U18 - 18mm Board

### ORDERING EXAMPLE

AM2BRKU15